

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



20 AUG 2004

(43) International Publication Date
4 September 2003 (04.09.2003)

PCT

(10) International Publication Number
WO 03/071968 A1

(51) International Patent Classification⁷: A61B 19/00, 17/16

(21) International Application Number: PCT/GB03/00817

(22) International Filing Date: 26 February 2003 (26.02.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0204549.0 27 February 2002 (27.02.2002) GB

(71) Applicant (for all designated States except US): DEPUY INTERNATIONAL LIMITED [GB/GB]; St Anthony's Road, Beeston, Leeds LS11 8DT (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A SURGICAL INSTRUMENT SYSTEM



(57) Abstract: A surgical instrument system includes a tool (2) including an elongate shaft which defines the tool axis. The shaft bears a plurality of marker rings (10, 11, 12) arranged in a predetermined pattern on the surface of the shaft so that they extend around the shaft axis. The system includes at least two receiving devices (14) which are spaced apart for receiving stereoscopic signals from the rings on the tool, and a data processor (16) for analysing the signal from the rings and generating information relating to the position and orientation of the tool relative to the receiving device.

WO 03/071968 A1

BEST AVAILABLE COPY